



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE STATED.
 NON-REFERENCED DIMENSION TOLERANCE IS ± 0.2 INCHES.
 Orival, Inc. reserves the right to modify filter dimensions without notice.

TECHNICAL DATA

MAXIMUM FLOW RATE:	175 GPM
AVAILABLE SCREEN MICRON SIZES:	50, 72, 100, 120, 150, 200, 400, 800, 1000, 1500, 3000
AREA STANDARD SCREEN:	302 SQ. INCHES
AREA HIGH PERFORMANCE SINTERED MULTI-LAYERED SCREEN:	453 SQ. INCHES
MAXIMUM WORKING PRESSURE:	125 PSIG
MAX. WORKING TEMPERATURE:	140 °F
INLET/OUTLET CONNECTIONS:	3" ASA FLANGED
DRAIN VALVE CONNECTION:	3/4" FEMALE
APPROX. EMPTY WEIGHT:	60 LBS
APPROX. FULL OF WATER WEIGHT:	--- LBS

DATA SHEET

ORM-030-IS

MANUALLY CLEANED FILTER

ORIVAL, INC.

213 S. VAN BRUNT ST.
 ENGLEWOOD, NJ 07631
 TEL (800) 567-9767, (201) 568-3311
 FAX (201) 568-1916
 filters@orival.com
 www.orival.com