



ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE STATED.  
 NON-REFERENCED DIMENSION TOLERANCE IS  $\pm 0.2$  INCHES.  
 Orival, Inc. reserves the right to modify filter dimensions without notice.

## TECHNICAL DATA

MAXIMUM FLOW RATE:	1320 GPM
AVAILABLE SCREEN MICRON SIZES:	50, 72, 100, 120, 150, 200, 400, 800, 1000, 1500, 3000
AREA STANDARD SCREEN:	870 SQ. INCHES
AREA HIGH PERFORMANCE SINTERED MULTI-LAYERED SCREEN:	1305 SQ. INCHES
MAXIMUM WORKING PRESSURE:	125 PSIG
MAX. WORKING TEMPERATURE:	140 °F
INLET/OUTLET CONNECTIONS:	8" FLANGED
DRAIN VALVE CONNECTION:	1.5" FEMALE
APPROX. EMPTY WEIGHT:	182 LBS
APPROX. FULL OF WATER WEIGHT:	--- LBS

## DATA SHEET

# ORM-080-IS

### MANUALLY CLEANED FILTER

**ORIVAL, INC.**  
 213 S. VAN BRUNT ST.  
 ENGLEWOOD, NJ 07631  
 TEL (800) 567-9767, (201) 568-3311  
 FAX (201) 568-1916  
 filters@orival.com  
 www.orival.com