


**FREE SPACE REQUIRED
FOR MAINTENANCE**



Orival Inc. reserves the right to modify filter dimensions without prior notice.

ALL DIMENSIONS IN INCHES UNLESS INDICATED

TECHNICAL DATA

MAXIMUM FLOW RATE:	27 G.P.M.
AVAILABLE SCREEN MICRON SIZES:	5, 10, 15, 25, 30, 40, 50, 80, 100, 120, 150, 200, 400, 800, 1000, 1500, 3000
OPEN AREA STD. SCREEN :	42 SQ. INCHES
OPEN AREA HIGH PERFORMANCE SINTERED MULTI-LAYERED SCREEN:	63 SQ. INCHES
MAXIMUM WORKING PRESSURE:	120 PSIG
MINIMUM INLET PRESSURE REQUIRED DURING RINSE CYCLE:	30 PSIG
MAX. WORKING TEMPERATURE:	150°F
INLET/OUTLET CONNECTIONS:	3/4" & 1" N.P.T.
DRAIN VALVE CONNECTION:	3/4" & 1" N.P.T.
DRAIN HEADER SIZE:	1" MINIMUM
APPROX. EMPTY WEIGHT:	52 LBS.
APPROX. FULL OF WATER WEIGHT:	65 LBS.

DATA SHEET

ORV-100-LE

AUTOMATIC SELF-CLEANING FILTER

OPTIONAL CONTROLLED OUTLET VALVE (C O V) FOR LOW FLOW AND / OR PRESSURE CONDITIONS
1" INLET, OUTLET AND DRAIN PORTS SHOWN. 3/4" ADAPTERS WILL ALSO BE SUPPLIED.

ORIVAL, INC.

213 S. VAN BRUNT ST.
ENGLEWOOD, N.J. 07631

TEL (800) 567-9767, (201) 568-3311

FAX (201) 568-1916

www.orival.com

filters@orival.com