



FREE SPACE REQUIRED FOR MAINTENANCE

FREE SPACE REQUIRED FOR INSTALLATION

2" RINSE VALVE

### TECHNICAL DATA

|  |  |
|--|--|
| MAXIMUM FLOW RATE:   | 800 G.P.M.   |
| AVAILABLE SCREEN MICRON SIZES:                                   | 5, 10, 15, 25, 30, 40, 50, 80, 100, 120, 150, 200, 300, 400, 800, 1000, 1500, 3000 |
| OPEN SCREEN AREA STANDARD SCREEN:                                | 826 SQ. INCHES   |
| OPEN SCREEN AREA HIGH PERFORMANCE MULTI LAYERED SINTERED SCREEN: | 1240 SQ. INCHES  |
| MAXIMUM WORKING PRESSURE:  | 150 PSIG   |
| MINIMUM INLET PRESSURE REQUIRED DURING RINSE CYCLE               | 30 PSIG  |
| MAX. WORKING TEMPERATURE:  | 150°F  |
| INLET/OUTLET FLANGES:  | 6" ANSI 150# RF  |
| DRAIN VALVE CONNECTION:  | 2"   |
| DRAIN HEADER SIZE:   | 2" MINIMUM   |
| APPROXIMATE WEIGHT - DRY:  | 635 LBS.   |
| APPROXIMATE SHIPPING WEIGHT:                                     | 805 LBS.   |
| APPROXIMATE WEIGHT FULL OF WATER:                                | 1080 LBS.  |

**ALL DIMENSIONS IN INCHES UNLESS INDICATED**  
Orival Inc. reserves the right to modify filter dimensions without prior notice.

## DATA SHEET

# ORZ-06-PX

### AUTOMATIC SELF-CLEANING FILTER

**ORIVAL, INC.**  
213 S. VAN BRUNT ST.  
ENGLEWOOD, N.J. 07631  
TEL (201) 568-3311, FAX (201) 568-1916  
[www.orival.com](http://www.orival.com)  
[filters@orival.com](mailto:filters@orival.com)